



Description

Anti-slip plywood is a durable panel ideal for demanding applications where high wear resistance is required, with a smooth reverse side coated with a resin impregnated film. It is weather and moisture resistant and is widely used for **transport, decoration, stages, anti-slip surfaces** and **furniture**. The new deep hexagonal pattern coating improves the panel's resistance to mechanical damage and wear, while providing a decorative appearance. The surface resists abrasion and commonly used chemicals.

Specifications

Properties	
Origin	Made in Vietnam
Structural Rating	Non structural
Wood Materials	Legally sourced plantation wood. FSC available on request
Film Color	Dark Brown, Black and Brown

Sizes (mm): 2440*1220 and 2500*1250

Nominal Thickness (mm)	9	12	15	17	18	20	21	24	27	30
Number of Plies	5	7	9	11	11	13	13	15	17	19

Film Density: Dynea film 60/180 GSM

Pattern	Hexa
Formaldehyde Emission Class	E1
Glue	Exterior, WBP, MUF (Melamine Urea Formaldehyde)
Edge Treatment	Waterproof Paint
Moisture Content	< 12%
Core Veneer	Acacia or Eucalyptus
Hardness	5900 -6800 MPA

Packaging

Characteristics	Dimension (mm): 2500*1250									
Thickness (mm)*	9	12	15	17	18	20	21	24	27	30
Number of boards per Pallet	100	76	60	54	52	46	44	38	33	30
Pallets per Container	16	16	16	16	16	16	16	16	16	16

Characteristics	Dimension (mm): 2440*1220									
Thickness (mm)*	9	12	15	17	18	20	21	24	27	30
Number of boards per Pallet	104	80	65	57	54	48	46	40	35	32
Pallets per Container	16	16	16	16	16	16	16	16	16	16

*Other thicknesses available on request.

Handling and Storage

Boards can be cleaned with warm water after use to remove any remaining material adhered to the surface. They must be stored on a hard, flat surface, avoiding direct contact with the ground and in a dry environment protected from water. Sudden changes in these conditions can affect the properties of the board. Separate the boxes from each other with clean, dry and resistant spacers of uniform thickness, suitable for loading/unloading with forklift.

