

Description

ECO FORMPLY – budget-friendly film-faced plywood built for reliable concrete construction. It offers essential durability without extra cost, suitable for **foundations, walls, floors, and another formwork**. Protective films improve moisture and wear resistance, ensuring strength, stability, and economical reuse in demanding projects.

Specifications

Properties	
Origin	Made in Vietnam
Structural Rating	Non structural
Wood Materials	Legally sourced plantation wood.
Film Color	Dark Brown, Black and Brown (Customers logo on request)

Sizes (mm): 2400*1200, 2440*1220 & 2500*1250

Nominal Thickness (mm)	9	12	15	17	18	20	21	24	27	30
Number of Plies	5	7	9	11	11	13	13	15	17	19

*Other sizes available on request.

Technical information	
Formaldehyde Emission Class	E1/ E2 EN 717-2:1995
Glue	WBP MUF (Melamine Urea Formaldehyde)
Film	165gsm
Thickness tolerance	EN 315: 2000
Core Veneer	100% Acacia
Length/Width tolerance	± 1.0 mm per meter
Squareness tolerance	± 1.0 mm per meter
Number of Cycles	Up to 7 times (double sides, full sheet)
Bonding Strength/Shearing test	EN 314 Class 2
Edge treatment	The edges are painted by brown/ black waterproof paint

Packaging


Characteristics	Dimension (mm): 2400*1200					
Thickness (mm)*	9	12	15	17	18	25
Number of boards per Pallet	108	83	67	58	56	40
Pallets per Container	16	16	16	16	16	16

Characteristics	Dimension (mm): 2440*1220									
Thickness (mm)*	9	12	15	17	18	20	21	24	27	30
Number of boards per Pallet	104	80	65	57	54	48	46	40	35	32
Pallets per Container	16	16	16	16	16	16	16	16	16	16

Characteristics	Dimension (mm): 2500*1250									
Thickness (mm)*	9	12	15	17	18	20	21	24	27	30
Number of boards per Pallet	100	76	60	54	52	46	44	38	33	30
Pallets per Container	16	16	16	16	16	16	16	16	16	16

*Other thicknesses available on request.





Handling & Storage Guidelines

Storage Conditions

Keep panels in a dry, clean, and well-ventilated environment. Avoid exposure to moisture, rain, or high temperatures. Store sheets horizontally on level, evenly spaced bearers, ensuring no direct ground contact to prevent warping and contamination.

Machining & Processing

Always use professional-grade tools for cutting, drilling, or shaping.

For optimal results, use a circular saw blade with approximately 350 mm diameter, 3.0–3.5 mm thickness, more than 100 teeth, and a rotation speed between 3,000 and 6,000 rpm.

Edge Protection

After any cutting or drilling, reseal all exposed edges with a suitable waterproof coating to maintain panel durability and prevent moisture ingress.

Handling Practices

Handle panels carefully during transportation and installation. Avoid dropping or rough handling, especially from height, to prevent structural damage and ensure jobsite safety.

Release Agent Application

Apply an appropriate formwork release agent prior to each concrete pour. This helps maintain a clean surface, simplifies stripping, and prolongs the service life of the plywood.

Installation Method

Fix panels using screws in combination with washers or support pads. Where possible, secure from the underside to protect the film surface. The use of nails is not recommended as it may damage the panel.

Cleaning & Maintenance

After use, clean panels promptly to remove any concrete residue. Use suitable tools and avoid aggressive methods that may damage the film surface or edges, ensuring longer reuse cycles.